



TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

Titanium Grade 2 Round bar
Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2
Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	58,6	
3,00 mm	h 7	44,9	
5,00 mm	h 7	1,1	(50,0)
6,00 mm	h 8	7,6	(500,0)
8,00 mm	h 8	163,0	(150,0)
10,00 mm	h 8	3,4	(1000,0)
12,00 mm	h 8	0,1	(300,0)
14,00 mm	h 8	3,7	(350,0)
15,00 mm	h 8	84,9	(150,0)
16,00 mm	h 9	1,6	(800,0)
18,00 mm	h 9	434,7	(300,0)
20,00 mm	h 9	415,8	(300,0)
22,00 mm	h 9	1,1	(400,0)
25,00 mm	h 9	16,4	(5000,0)
30,00 mm	h 9	49,4	(300,0)
35,00 mm	h 9	4,4	(800,0)
40,00 mm	-0/+0.100	1433,5	(2000,0)
45,00 mm	-0/+0.100	8,1	(700,0)
50,00mm	-0/+0.100	678,2	
55,00 mm	-0/+0.100	1542,3	
60,00 mm	-0/+0.120	1226,0	
65,00 mm	-0/+0.120	660,7	
70,00 mm	-0/+0.140	366,4	(200,0)
80,00 mm	-0/+0.140	359,1	(300,0)
90,00 mm	-0/+0.200	242,4	
100,00 mm	-0/+0.500	395,0	
110,00 mm	-0/+0.500	341,7	
120,00 mm	-0/+0.500	213,1	(150,0)
130,00 mm	-0/+0.500	537,3	
140,00 mm	-0/+0.500	5,8	(420,0)
150,00 mm	-0/+0.500	32,1	(240,0)
160,00 mm	-0/+0.500	267,0	
170,00 mm	-0/+0.500	508,3	
180,00 mm	-0/+0.500	231,3	
190,00 mm	-0/+0.500	141,5	



TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
200,00 mm	-0/+0.500	69,9	(280,0)
225,00 mm	-0/+0.500	20,3	(280,0)
250,00 mm	-0/+0.500	9,0	(333,0)
280,00 mm	-0/+0.500	20,7	
305,00 mm	-0/+0.500	35,2	
350,00 mm	-0/+0.500	219,4	

Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	328,0	
130,00 mm	-0/+0.500	236,8	

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	22,4	(30,0)
3,00 mm	h 7	200,8	
4,00 mm	h 7	1,2	(200,0)
5,00 mm	h 7	65,1	(400,0)
6,00 mm	h 8	0,9	(800,0)
8,00 mm	h 8	124,6	(150,0)
10,00 mm	h 8	45,7	(250,0)
12,00 mm	h 8	43,8	(300,0)
14,00 mm	h 8	213,1	
15,00 mm	h 8	299,7	
16,00 mm	h 9	272,7	(400,0)
18,00 mm	h 9	0,5	(300,0)
20,00 mm	h 9	388,5	(1100,0)
22,00 mm	h 9	361,0	
25,00 mm	h 9	549,9	(1600,0)
30,00 mm	h 9	363,2	
35,00 mm	h 9	668,5	(600,0)
36,00 mm	h 9	0,6	(400,0)
40,00 mm	-0/+0.100	102,1	(2300,0)



TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
40,00 mm	-0/+0.100	101,8	(2300,0)
45,00 mm	-0/+0.100	167,5	(200,0)
50,00 mm	-0/+0.100	11,5	(1200,0)
55,00 mm	-0/+0.100	141,1	(200,0)
60,00 mm	-0/+0.120	3,2	(800,0)
65,00 mm	-0/+0.120	3,9	(500,0)
70,00 mm	-0/+0.140	24,2	(600,0)
75,00 mm	-0/+0.140	349,1	(300,0)
80,00 mm	-0/+0.140	198,5	(400,0)
90,00 mm	-0/+0.200	69,8	(500,0)
100,00 mm	-0/+0.500	1775,5	
110,00 mm	-0/+0.500	495,0	
120,00 mm	-0/+0.500	146,6	(150,0)
130,00 mm	-0/+0.500	4,0	(1040,0)
140,00 mm	-0/+0.500	81,7	(420,0)
150,00 mm	-0/+0.500	292,0	
160,00 mm	-0/+0.500	258,7	
170,00 mm	-0/+0.500	520,8	
180,00 mm	-0/+0.500	410,3	
190,00 mm	-0/+0.500	207,4	
200,00 mm	-0/+0.500	48,7	(300,0)
225,00 mm	-0/+0.500	11,1	
230,00 mm	-0/+0.500	287,3	
250,00 mm	-0/+0.500	151,0	
280,00 mm	-0/+0.500	146,0	
305,00 mm	-0/+0.500	312,5	
350,00 mm	-0/+0.500	119,6	(215,0)

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASM SB 265 Gr1 edition 2015 DIN 17860 / NACE

MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Contidition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
0,6 x 1000 x 2500	767,7	
0,8x 1000 x 2500	542,1	
1,0 x 1250 x 3000	1777,0	(800,0)



TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASM SB 265 Gr1 edition 2015 DIN 17860 / NACE MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Condition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
1,5 x 1250 x 3000	1067,9	(500,0)
2,0 x 1250 x 3000	198,6	
2,0 x 1250 x 3000	468,1	(1502,0)
2,5 x 1250 x 3000	212,6	
3,0 x 1250 x 3000	509,8	(500,0)
4,0 x 1000 x 2000	292,3	(500,0)
5,0 x 1000 x 2000	240,7	(180,0)
6,0 x 1000 x 2000	214,5	

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017
PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
1,0x1000x2000	146,4	(200,0)
1,0x1000x2000	8,2	
1,5x1000x2000	41,0	(600,0)
2,0x1000x2000	1524,9	
3,0x1000x2000	840,9	
4,0x1000x2000	364,4	
5,0x1000x2000	424,1	
5,0x1000x2000	271,6	

Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1 x 1000 x 2000	35,6	(100,0)
1 x 1000 x 2000	118,8	
1 x 1000 x 2000	13,5	
2 x 1000 x 2000	89,1	(280,0)
3 x 1000 x 2000	80,8	(300,0)
3 x 1250 x 2500	206,0	
4 x 1000 x 2000	36,0	(72,0)
5 x 1000 x 2000	91,6	



TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	105,8	
12,7 x 12,7	14,4	(150,0)
19,05 x 19,05	39,6	(100,0)
25,4 x 6,35	42,4	(100,0)
25,4 x 12,7	0,0	(300,0)
25,4 x 25,4	322,2	

Titanium Grade 2 Welding wire

AWS A5.16 ERTi-2

Dimension	QTY (kg)	Incoming
1,2 mm	15,0	
1,2 mm	15,0	
2,0 mm	15,0	
2,4 mm	10,0	
3,2 mm	20,0	

Titanium Grade 5 Welding wire

AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
1,6 mm	10,0	
2,4 mm	10,0	